



# Silkolene®

## Classic Technical Data

## Chatsworth Engine Oils

Chatsworth Engine oils are manufactured from blends of high quality base oils and modern additive systems. They are suitable for use in naturally aspirated diesel and petrol engines in certain classic and vintage vehicles.

Chatsworth Engine Oils may also be used in many stationary engines operating under moderate service conditions.

- Controlled detergency/dispersency to give less carbon build up and for effective sludge control.
- Good thermal and oxidation stability.

Typical Technical Data	Chatsworth 30	Chatsworth 40
SAE	30	40
US Military	MIL-L-2104B	MIL-L-2104B
American Petroleum Institute (API) Classification	API CC/SD	API CC/SD
Kinematic Viscosity @ 100°C cSt	11.5	14.0
Kinematic Viscosity @ 40°C cSt	102	136.7
Viscosity Index	99	99
Pour point °C	-28	-25
Closed Flash point °C	190	200
Specific gravity @ 15°C	0.887	0.894



The information contained herein is believed to be correct at the time of publication. No warranty, expressed or implied, is given concerning the accuracy of the information or suitability of the products. Fuchs Silkolene reserves the right to modify and change its products and specifications without prior notice. Full Material Safety Data Sheets are available on request from the Fuchs Lubricants (UK) Technical Services Department on FREEPHONE 0800 212542 or Tel No: +44 (0)1782 203085