



Silkolene®



Maintain Technical Data

Pro Cool

Advanced all season non toxic engine coolant

Silkolene Pro Cool is a ready-to-use high performance automotive antifreeze and engine coolant for all year round use. The product is based on propylene glycol and hence gives a very safe level of toxicity when compared to ethylene glycol based anti-freezes. The Pro Cool formulation includes 50% distilled water to give zero limescale deposits, optimum frost protection in severe winter conditions plus excellent anti-corrosion performance.

The balanced inhibitor system incorporated in Silkolene Pro Cool is the result of several years research and development and is designed to protect the cooling system against foaming, scale formation and corrosion. Anti-cavitation performance exceeds that of conventional ethylene glycol based anti-freezes, providing the user with superior protection against engine and coolant pump damage due to this phenomenon.

Do not dilute Silkolene Pro Cool with water. This will reduce its anti-corrosion performance and frost protection level.

Pro Cool is compatible with all alloys, plastics, elastomers and gasket materials used in modern engine cooling systems.



Typical Technical Data

Typical Technical Data	PRO COOL
Appearance	Clear Blue Liquid
Specific Gravity @ 20°C	1.048
Refractive Index @ 20°C	1.388
Freezing Protection...°C	-32

The information contained herein is believed to be correct at the time of publication. No warranty, expressed or implied, is given concerning the accuracy of the information or suitability of the products. Fuchs Silkolene reserves the right to modify and change its products and specifications without prior notice. Full Material Safety Data Sheets are available on request from the Fuchs Lubricants (UK) Technical Services Department on FREEPHONE 0800 212542 or Tel No: +44 (0)1782 203085

Fuchs Lubricants (UK) PLC Century Street, Hanley, Stoke on Trent, ST1 5HU Tel No: +44 (0)8701 200400 Fax: +44 (0)1782 203775 www.silkolene.com