



## SILKOLENE GEAR 75W-90

### For Manual Gearboxes And Final Drive Units In Most Modern Vehicles

#### Description

SILKOLENE GEAR 75W-90 is a high performance semi synthetic gear oil suitable for use in gearboxes and final drive units fitted to many modern cars and commercial vehicles.

The latest technology is utilised to give excellent performance in both synchromesh gearboxes and heavily loaded final drive units. The semi synthetic base oils give further improvements in thermal stability and load carrying ability.

Very shear stable viscosity modifiers ensure minimal viscosity loss and optimum protection under all conditions and at all temperatures.

#### Advantages / Benefits

- Total driveline oil.
- Suitable for gearboxes and hypoid axles.
- Smooth gearshifting at all temperatures.
- Maintains viscosity under all conditions.

#### Specifications

- |       |        |
|-------|--------|
| • SAE | 75W/90 |
| • API | GL4    |
|       | GL5    |



June 2002 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.

# Product INFORMATION

FUCHS (UK) PLC.  
New Century Street  
Hanley  
GB-Stoke-on-Trent,  
Staffordshire, ST1 5HU



## Typical Data: SILKOLENE GEAR 75W-90

Characteristics	Unit		Test Method
Colour		Clear amber	ASTM D1500
Kinematic viscosity @ 100°C	mm <sup>2</sup> /s	14.3	IP71
@ 40°C	mm <sup>2</sup> /s	85.0	
Viscosity index		175	IP226
Flash point (PMCC)	°C	200	IP34
Specific gravity @ 15.6°C		0.889	IP160
Pour point	°C	- 40	IP15

June 2002 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.