



TITAN GT1 PRO C-3 5W-30

Specially developed for VW and Mercedes-Benz vehicles with exhaust after treatment and turbocharger

Description

Premium Motor Oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for VW and Mercedes-Benz vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimised exhaust emissions.

Continued on Page 2

Application

TITAN GT1 PRO C-3 5W-30 fulfils all the requirements of engine oils for vehicles fitted with exhaust treatment systems.

TITAN GT1 PRO C-3 5W-30 is fully miscible with other engine oils. However, mixing with other engine oils should be avoided because this can reduce or even eliminate the benefits offered.

We recommend that manufacturer's oil change intervals should be observed to generate the best possible economy and service life.

Advantages/Benefits

- Very low levels of sulphated ash, phosphorous and sulphur protect and extend the service time of all exhaust treatment systems
- Excellent protection against wear in advanced, highly-stressed diesel and gasoline engines
- Universal use in gasoline and diesel engines which are designed to be operated with fuel-economy engine oils
- Reduces pollutant emissions
- Reduces the formation of deposits in engines and turbochargers. This increases reliability and lowers maintenance costs
- Low evaporation losses lower oil consumption

Specifications/Approvals

- ACEA A3/B4
- MB-APPROVAL 229.51
- VW 504 00 / 507 00

Fuchs Recommendations

- ACEA C3*
- *differing phosphorus content



Description (continued)

TITAN GT1 PRO C-3 5W-30 is an innovative, premium motor oil for today's cars. The combination of a number of valuable characteristics in one product makes TITAN GT1 PRO C-3 5W-30 an exceptional oil.

So TITAN GT1 PRO C-3 5W-30 meets the requirements of the VW specifications 504 00 / 507 00 and the requirements of the Mercedes-Benz specification MB-APPROVAL 229.51. TITAN GT1 PRO C-3 5W-30 offers benefits to all advanced, fuel-efficient engines regardless of their emission category. TITAN GT1 PRO C-3 5W-30 keeps turbochargers clean for maintaining long-term optimum charging pressure. TITAN GT1 PRO C-3 5W-30 provides perfect protection of exhaust treatment devices like particulate filters, CRT's or oxidation catalysts. TITAN GT1 PRO C-3 5W-30 guarantees low fuel consumption. These advantages are applicable for all vehicles where ACEA C3 engine oils are specified.

CHARACTERISTICS: TITAN GT1 PRO C-3 5W-30

Density at 15°C	DIN 51757	0.849 g/ml
Kinematic Viscosity at 40°C	DIN 51562-1	71.1 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	11.6 mm ² /s
Viscosity Index	DIN ISO 2909	155
Flash Point, CoC	DIN ISO 2592	210°C
Pour Point	DIN ISO 3016	-42°C

April 2008 GDUK Page 2 of 2

Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products